




Drive Type Fastenings without Taper Action
Woodruff Keys
Dimensions and Application

DIN
6888

Mitnehmervverbindungen ohne Anzug; Scheibenfedern, Abmessungen und Anwendung

Dimensions in mm



Breaking of corners
(all-round)
Chamfering RADIUSING
at manufacturer's choice

Radius at bottom of keyway
in shaft and hub

Designation of a Woodruff key of width $b = 4$ mm and height $h = 5$ mm:

Woodruff key 4 x 5 DIN 6888




Cross-section of Woodruff key (Half-round steel according to DIN 6882)		Width b h9	1	1,5	2	2,5 ^{*)}	3			4			
		Height h h12	1,4	2,6	2,6	3,7	3,7	5	6,5	5	6,5	7,5	
Allocation ¹⁾	I	for shaft diameter d_1	above	3	4	6	8			10			
		up to	4	6	8	10			12				
	II	for shaft diameter d_1	above	6	8	10	12			17			
		up to	8	10	12	17			22				
Diameter		d_2	4	7	7	10	10	10	13	16	13	16	19
Perm. var.			- 0,1	- 0,1	- 0,1	- 0,1	- 0,1			- 0,1			
Chamfering or radiusing		r_1	0,2	0,2	0,2	0,2	0,2			0,2			
Perm. var.			+ 0,1	+ 0,1	+ 0,1	+ 0,1	+ 0,1			+ 0,1			
Length		$l \approx$	3,82	6,76	6,76	9,66	9,66	9,66	12,65	15,72	12,65	15,72	18,57
Weight (7.85 kg/dm ³) kg/1000 pieces \approx			0,031	0,153	0,204	0,414	0,518	0,622	1,10	1,80	1,47	2,40	3,27
Shaft keyway	Width $b^2)$	Tight fit P9	1	1,5	2	2,5	3			4			
		Sliding fit N9	1	1,5	2	2,5	3			4			
	Depth $t_1^3)$	Series A	1	2	1,8	2,9	2,9	2,5	3,8	5,3	3,5	5	6
		Series B	1	2	1,8	2,9	2,9	2,8	4,1	5,6	4,1	5,6	6,6
		Perm. var. for A and B	+ 0,1	+ 0,1	+ 0,1	+ 0,1	+ 0,1			+ 0,1			
Diameter $d_2 + 0,5$			4	7	7	10	10	10	13	16	13	16	19
Hub keyway	Width $b^2)$	Tight fit P9	1	1,5	2	2,5	3			4			
		Sliding fit J9 ⁶⁾	1	1,5	2	2,5	3			4			
	Depth $t_2^3)$	Series A ⁴⁾	0,6	0,8	1	1	1,4			1,7			
		Series B ⁵⁾	0,6	0,8	1	1	1,1			1,1			
		Perm. var. for A and B	+ 0,1	+ 0,1	+ 0,1	+ 0,1	+ 0,1			+ 0,1			
Radius at bottom of keyway		r_2	0,2	0,2	0,2	0,2	0,2			0,2			
Perm. var.			- 0,1	- 0,1	- 0,1	- 0,1	- 0,1			- 0,1			

^{*)} Only for automotive applications

Material: St 60 (steel having a tensile strength of at least 60 kg/mm² in the finished condition). alternative materials to be specified in order

- Where corresponding dimensions are involved, particularly for shaft extensions, allocation of the Woodruff key cross-sections appropriate to the shaft diameters concerned must be observed. Allocation I applies in all cases where the Woodruff key is used in the role of a feather key, i.e. to transmit the whole of the torque. Allocation II applies in all cases where the Woodruff key is used solely for locating the driving element, other elements, e.g. cotters or tapers being employed to transmit the torque.
- The listed permissible variations for keyway widths are intended for guidance only. It is recommended that for the widths of broached keyways ISA Class IT 8 be observed instead of IT 9 (similarly P8 instead of P9, N8 instead of N9 and J8 instead of J9).
- In workshop drawings the dimensions t_1 and $(d_1 - t_1)$, also t_2 and $(d_1 + t_2)$ may appear side by side; however, in many cases the dimensions t_1 and $(d_1 + t_2)$ will suffice. In this connection it may be necessary to allow for permissible variations and machining allowances on the shaft and hub bore.
- Preference should be given to Series A (deep hub keyway); this conforms to DIN 6885 Sheet 1 (t_2 with back clearance).
- Series B (shallow hub keyway) for machine tools; this conforms to DIN 6885 Sheet 2.
- When the relationship between the Woodruff key and the shaft diameter is based on Allocation II it is permissible to use tolerance zone D 10 also.


Continued on page 2



Designation of a Woodruff key of width $b = 8 \text{ mm}$ and height $h = 11 \text{ mm}$:
Woodruff key 8×11 DIN 6888

Breaking of corners
(all-round)
Chamfering RADIUSING
at manufacturer's choice

Radius at bottom of keyway
in shaft and hub



Cross-section of Woodruff key (Half-round steel according to DIN 6882)		Width b h9			6				8			10				
Height h h12		6,5	7,5	9	7,5	9	(10)	11	9	11	13	11	13	16		
Allocation ¹⁾	I for shaft diameter d_1 above up to	12	17	—	17	—	—	22	—	—	30	—	—	—		
	II for shaft diameter d_1 above up to	22	30	—	30	—	—	30	—	—	38	—	—	—		
Diameter	d_2	16	19	22	19	22	25	28	22	28	32	28	32	45		
	Perm.var.	-0,1			-0,1			-0,2			-0,2			-0,2		
Chamfering or radiusing	r_1	0,2			0,4				0,4			0,4				
	Perm.var.	+0,1			+0,2				+0,2			+0,2				
Length	$l \approx$	15,72	18,57	21,63	18,57	21,63	24,49	27,35	21,63	27,35	31,43	27,35	31,43	43,08		
Weight	$(7,85 \text{ kg/dm}^3) \text{ kg/1000 p.} \approx$	3,01	4,09	5,73	4,91	6,88	8,64	10,6	9,17	14,1	19,3	17,6	24,1	39,9		
Shaft keyway	Width $b^2)$	Tight fit P9	5			6				8			10			
		Sliding fit N9	5			6				8			10			
	Depth $t_1^3)$	Series A	4,5	5,5	7	5,1	6,6	7,6	8,6	6,2	8,2	10,2	7,8	9,8	12,8	
		Series B	5,4	6,4	7,9	6	7,5	8,5	9,5	7,5	9,5	11,5	9,1	11,1	14,1	
	Perm.var. for A and B	+0,1		+0,2		+0,1		+0,2		+0,2			+0,2			
	Diameter $d_2 + 0,5$	16	19	22	19	22	25	28	22	28	32	28	32	45		
Hub keyway	Width $b^2)$	Tight fit P9	5			6				8			10			
		Sliding fit J9 ⁶⁾	5			6				8			10			
	Depth $t_2^3)$	Series A ⁴⁾	2,2			2,6				3			3,4			
		Perm.var. for A	+0,1			+0,1				+0,1			+0,2			
		Series B ⁵⁾	1,3			1,7				1,7			2,1			
	Perm.var. for B	+0,1			+0,1				+0,1			+0,1				
	Radius at bottom of keyway r_2	0,2			0,4				0,4			0,4				
	Perm.var.	-0,1			-0,2				-0,2			-0,2				

- Bracketed values should be avoided as far as possible.
Material: St 60 (steel having a tensile strength of at least 60 kg/mm^2 in the finished condition), alternative materials to be specified in order
- Where corresponding dimensions are involved, particularly for shaft extensions, allocation of the Woodruff key cross-sections appropriate to the shaft diameters concerned must be observed. Allocation I applies in all cases where the Woodruff key is used in the role of a feather key, i.e. to transmit the whole of the torque. Allocation II applies in all cases where the Woodruff key is used solely for locating the driving element, other elements, e.g. cotter pins or tapers being employed to transmit the torque.
 - The listed permissible variations for keyway widths are intended for guidance only. It is recommended that for the widths of broached keyways ISA Class IT 8 be observed instead of IT 9 (similarly P8 instead of P9, N8 instead of N9 and J8 instead of J9).
 - In workshop drawings the dimensions t_1 and $(d_1 - t_1)$, also t_2 and $(d_1 + t_2)$ may appear side by side; however, in many cases the dimensions t_1 and $(d_1 + t_2)$ will suffice. In this connection it may be necessary to allow for permissible variations and machining allowances on the shaft and hub bore.
 - Preference should be given to Series A (deep hub keyway); this conforms to DIN 6885 Sheet 1 (t_2 with back clearance).
 - Series B (shallow hub keyway) for machine tools; this conforms to DIN 6885 Sheet 2.
 - When the relationship between the Woodruff key and the shaft diameter is based on Allocation II it is permissible to use tolerance zone B 10 also.